## **TeamBoard** Windows OPS i7 - 12th Gen (UHD Support)



TM-0PS-i7-12



## **Overview**

The TeamBoard Windows OPS for Interactive Displays and Digital Signage is the latest OPS product designed according to Intel<sup>®</sup> OPS standard.

It provides the ideal solution for all-in-one touch PC or interactive panel applications.



## **Features**

- Supports Alder Lake-P 12th Gen Intel Core™ i7 CPU
- Windows 10, Windows 11, Windows Linux
- Integrated Intel® Iris® Xe Graphics
- Supports DP/HDMI Sync & Async Dual Display
- Supports One-key Backup & Restore OS by BIOS
- Supports One-key Restore OS by Hardware
- Supports M.2 SATA & M.2 NVME Dual Protocols
- Supports JAE 80PIN Interface
- Supports TPM 2.0
- Warranty Refer to your local distributor

## **TeamBoard** Windows OPS i7 – 12th Gen (UHD Support)



CONFIGURATION	
CPU	12th Gen Intel Core™ i7 CPU
Memory	1 x SO-DIMM DDR4 3200MHz 16GB memory
Chanada	1 x M.2 2280 size for NVMe/SATA SSD (256GB)
Storage	1 x 2.5" SATA HDD/SDD
GPU	Intel® Iris® Xe Graphics
Display	Support DP/HDMI, 3 Simultaneous Displays
Audio	Realtek HD audio 5.1 channel
NETWORK	
	1. Dealtak 01111 Call av Intel Ethernet Connection 1990 M
LAN WIFI	1 x Realtek 8111H Co-Lay Intel Ethernet Connection I226LM 1 x M.2 2230 for Wi-Fi + Bluetooth
WIFI	1XM.2225010FW1-F1+Bluetooth
I/O INTERFACE	
French	1x DP 1.4, 1x HDMI 1.4, 2 x USB 2.0, 2 x USB 3.1, 1 x Type-C , 1 x RJ45,
Front	1x Line out & MIC-In 2-in-1 connector, 2 x Wi-Fi/BT ANT
Rear	1xJAE 80PIN HDMI2.0 out(4K/60Hz)
POWER	
Input	12~19V DC IN, 2.5/5.5 DC Jack & JAE 80Pin DC IN
SIZE	
Dimension(mm)	The bare: 119*180*30mm   Packing cases 282*257*79mm
Weight (Kg)	Net weight≈0.75Kg   Gross weight≈1.0Kg
TEMPERATURE & HUMIDITY	
Working temperature	5°C~45°C
Working humidity	10% - 95% @40°C No condensation
Storage temperature	-20°C~70°C
Storage humidity	5% - 95% @40°C No condensation
0S	
Supported OS	Windows 10/11, Linux



**Remark:** Above mentioned parameters are for Standard models and are subject to change without notice.\*