


65" PCAP Interactive Panel

TEAM
BOARD

TM 65 PRO



Overview

TeamBoard PCAP Interactive Panel is the new capacitive technology screen generation that offers the best interactive experience with a stunning leading-edge visual performance. PCAP Interactive Panel incorporates PCAP technology with 'zero air gap' feature for a seamless experience. The screen offers up to 60 points of touch.

TeamBoard PCAP Interactive Panel is the new bonded capacitive touch technology for the most natural, responsive, and smooth touch experience. The PCAP Pro's sleek 'edge to edge' design allows users to effectively utilise the screen technology in portrait, landscape, or table mode.

There are ample I/O ports that would suit any audio-visual environment, making the PCAP Interactive Panel a must-have companion for education, government, and the corporate sector. PCAP multi-touch screens come ready for easy wall or trolley installation.



Features

- Optically bonded - zero airgap
- Multi-touch – 60 touchpoints
- Edge-to-edge slimline profile
- Compatible with Windows, MAC, Android and Chromebook
- 4K resolution (3840 x 2160px)
- Integrated OPS PC Slot (PC units sold separately)
- Mount in landscape, portrait or table mode
- Mobile and electric height-adjustable options are available
- Warranty - Refer to your local distributor

65" PCAP - Interactive Panel

TEAM
BOARD

TM 65 PRO

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| Resolution | Up to 3840 x 2160 @ 60Hz |
| Display Features | Direct LED |
| Screen dimension | 65" (64.53") |
| Set dimension | 1493.5mm (W) x 875.8mm (H) x 83.1mm (D) |
| Temperature / Humidity | 0°C ~ 40° / 20 - 80%RH (No Condensation) |
| Net weight | 40Kgs |
| Aspect Ratio | 16:9 |
| Brightness | 500 cd/m ² |
| Contrast | 1200:1 |
| Colours | 10bit, 1.07 Billion colours |
| View Angle | 178°/ 178° (H/V) |
| Support Resolution | 4K Ultra HD 3840 x 2160 @60Hz |
| Voltage range | AC 100-240V ~ 50/60Hz |
| Power Consumption | Standby Power <=0.5W - Rated Power < 230W |
| Audio | 15W x 2 (RMS) |
| VESA mount | 600 x 400 mm, M8 Screw |
| Panel Response Time | 8 ms |
| Service Life | > 30,000 Hours |
| Installation | Landscape |

CONNECTIVITY

SIDE

| | |
|-------------------|--------------------|
| HDMI 2.0 Input(s) | 2 (HDMI1/ARC) |
| USB 2.0 | 1 |
| Headphone Output | 1 (Mini Jack) |
| Audio In | 1 (Mini Jack) |
| RS-232C Port | 1 (DB-9F) |
| Touch Out | 1 (USB type B 2.0) |
| OPS Slot | 1 |

COVER GLASS

| | |
|-----------|-----|
| Thickness | 4mm |
| Hardness | 7H |

TOUCH PARAMETERS

| | |
|------------------------|------------------------|
| Touch Technology | P-CAP Bonded |
| Touch Points | 60 Point (Windows) |
| Writing Mode | Finger, capacitive pen |
| Response Time | 10ms |
| Positioning Resolution | 32768 X 32768 |
| Connection Port | USB+UART |
| PC response | System auto response |

PHYSICAL SPECIFICATIONS

| | |
|--------------------|---|
| Package Dimensions | 1615mm (W) x 1000mm (H) x 230mm (D) |
| Gross Weight | 47Kgs |
| Screen Dimensions | 1493.5mm (W) x 875.8mm (H) x 83.1mm (D) |
| Net Weight | 40Kgs |



MOBILITY solutions

At TeamBoard we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remark:

Above mentioned parameters are for Standard models and are subject to change without notice. *