

92" Ultimate Interactive Panel

TEAM
BOARD

TM-FX-92



Overview

- TeamBoard Ultimate Interactive Panel (21:9) incorporates 20 points of touch with the a slim IR technology.
- Complete with Windows mini OPS (sold separately), the system is completely plug and play, with no drivers necessary for interaction.
- All TeamBoard panels work with Windows, OSX and Linux operating systems.
- The screen is 5K resolution, high brightness LED backlight and ultrawide screen format (21:9).
- Provides an ideal medium for presentation, interaction and collaboration with different sources.
- The ultrawide aspect ratio offers more horizontal space to work with, which proves to be exceptionally useful in productivity tasks.
- TeamBoard interactive flat panels come ready for easy wall or trolley installation.



Features

- 5K native resolution (5120 x 2880px)
- Optical Slim IR Technology
- Multi-touch – Up to 20 touch points
- 21:9 Aspect ratio
- 2 x 15 Watts integrated speakers
- 3mm toughened glass
- Integrated Mini OPS Slot (Mini OPS units sold separately)
- Mini OPS available for great performance
- Ready for easy wall or trolley installation
- Warranty - Refer to your local distributor

92" Ultimate Interactive Panel

**TEAM
BOARD**

TM-FX-92

TECHNICAL SPECIFICATIONS

Resolution	Up to 5120 x 2160 px @ 60Hz
Display Features	DLED
Screen dimension	92"
Aspect Ratio	21:9
Dimensions	2203mm (L) x 964mm (H) x 100mm (W)
Temperature / Humidity	0°C ~ 40°
Net weight	65±1kg
Brightness	450cd/m ²
Contrast	5000:1
Colours	8bit+FRC, 1.07G
VGA/HDMI Input Support resolution:	640*480/800*600/1024*768/1280*768/1280*800/1280*960/1280*1024/1360*768/1440*900/1600*1200/1920*1080@60Hz/ 3840*2160@30Hz/3840*2160@60Hz/5120*2160@60Hz
View Angle	178°
Power range	Stand by Power <0.5W - Max power: 780W (With OPS) / 710W (Without OPS)
Voltage range	Rating 100- 240V~, 50/60Hz
Speaker	2.0 channel (2*15W)
VESA mount	1000 x 500 mm

I/O PORTS

HDMI 2.0	1 - Max 3840x2160@60Hz
OPS Slot	1 - Max 5120x2160@60Hz
DP 1.4 (IN)	1 - Max 5120x2160@60Hz
USB-A 2.0	4
USB-B	1
USB-C	1 - Charge support max PD2.0 65W @20V/3.25A, Display support up to 5120x2160@60Hz, Touch support USB 2.0, USB Display not supported
RS232	1 - Via RJ45 Port
LAN IN	1
Optical	1
DP 1.4 (OUT)	1 - Max 5120x2160@60Hz
Earphone	1

TOUCH PARAMETERS

Touch points	Up to 20 point multi touch
Writing mode	Finger, stylus or any non-transparent object
Positioning technology	IR technology
Positioning accuracy	<2mm
Positioning resolution	4096*4096/16384*16384/32768*32768
Response Size	≥φ3mm
Touch interface	USB
Operating system	Windows/Linux/MAC/Android
Response Time	<10ms

GLASS

Thickness	4mm (Anti-Glare)
Toughness	8H (Mohs)

SCREEN PACKAGE

Dimensions	2395mm (L) x 185mm (W) x 1100mm (H)
Gross weight	83±1.5 KG

INSIDE THE BOX

Remote controller	1
Power cable (1.8m)	1
Touch pen	2
DP Cable (2m)	1
USB (touch USB 1.5m)	1

**Mobility
solutions**

At TeamBoard we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remark: Above mentioned parameters are for Standard models and are subject to change without notice. * Not all applications are compatible with Android 8.0.