

TEAM
BOARD

PCAP Interactive Panel



PRODUCT CODE

TM-PRO-65 | TM-PRO-75 | TM-PRO-86

TECHNICAL SPECIFICATIONS

	TeamBoard PCAP 65"	TeamBoard PCAP 75"	TeamBoard PCAP 86"
Resolution	Up to 3840 x 2160 @ 60Hz	Up to 3840 x 2160 @ 60Hz	Up to 3840 x 2160 @ 60Hz
Display Features	Direct LED	Direct LED	Direct LED
Screen Dimension	65" (64.53")	75" (74.52")	86" (85.6")
Temperature	0°C ~ 40° 20 - 80%RH (No Condensation)	0°C ~ 40° 20 - 80%RH (No Condensation)	0°C ~ 40° 20 - 80%RH (No Condensation)
Aspect Ratio	16:9	16:9	16:9
Brightness	500 cd/m2	500 cd/m2	500 cd/m2
Contrast	1200:1	1200:1	1200:1
Colours	10bit, 1.07 Billion colours	10bit, 1.07 Billion colours	10bit, 1.07 Billion colours
View Angle	178° / 178°(H/V)	178° / 178°(H/V)	178° / 178°(H/V)
Support Resolution	4K Ultra HD 3840 x 2160 @60Hz	4K Ultra HD 3840 x 2160 @60Hz	4K Ultra HD 3840 x 2160 @60Hz
Input Voltage	AC 100-240V~50/60Hz	AC 100-240V~50/60Hz	AC 100-240V~50/60Hz
Power Consumption	Standby Power <=0.5W - Rated Power < 230W	Standby Power <=0.5W - Rated Power < 300W	Standby Power <=0.5W - Rated Power < 370W
Audio	2 x 15W (RMS)	2 x 15W (RMS)	2 x 15W (RMS)
VESA Mount	600 x 400mm, M8 Screw	800 x 600mm, M8 Screw	800 x 600mm, M8 Screw
Panel Response Time	8ms	8ms	8ms
Service Life	> 30,000 Hrs	> 30,000 Hrs	> 30,000 Hrs
Installation	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait

CONNECTIVITY

HDMI 2.0 IN	2 x Side (HDMI 1/ARC)	2 x Side (HDMI 1/ARC)	2 x Side (HDMI 1/ARC)
USB 2.0	1 x Side	1 x Side	1 x Side
Audio Output	1 x Side (Mini Jack)	1 x Side (Mini Jack)	1 x Side (Mini Jack)
Audio IN	1 x Side (Mini Jack)	1 x Side (Mini Jack)	1 x Side (Mini Jack)
USB - C	1 x Side	1 x Side	1 x Side
RS232	1 x Side (DB-9F)	1 x Side (DB-9F)	1 x Side (DB-9F)

	TeamBoard PCAP 65"	TeamBoard PCAP 75"	TeamBoard PCAP 86"
Touch Out	1 x Side (USB type B 2.0)	1 x Side (USB type B 2.0)	1 x Side (USB type B 2.0)
OPS Slot	1 x Side	1 x Side	1 x Side

TOUCH SPECIFICATIONS

Touch Technology	P-CAP Bonded	P-CAP Bonded	P-CAP Bonded
Touch Points	60 Touch Points (Windows)	60 Touch Points (Windows)	60 Touch Points (Windows)
Writing Mode	Finger or Capacitive Pen	Finger or Capacitive Pen	Finger or Capacitive Pen
Response Time	10ms	10ms	10ms
Positioning Resolution	32768 X 32768	32768 X 32768	32768 X 32768
Connection Port	USB+UART	USB+UART	USB+UART

COVER GLASS

Thickness	3mm	3mm	3mm
Hardness	7H	7H	7H

PHYSICAL SPECIFICATIONS

Package Dimensions	63.5" (W) x 39.3" (H) x 9" (D) 1615 (W) x 1000 (H) x 230 (D) mm	72.4" (W) x 44.3" (H) x 9" (D) 1839 (W) x 1127 (H) x 230 (D) mm	82" (W) x 49.7" (H) x 9" (D) 2084 (W) x 1264 (H) x 230 (D) mm
Gross Weight in Box	47Kgs / 103.6lb	60Kgs / 132.2lb	73Kgs / 160.9lb
Screen Dimensions	58.7" (W) x 34.4" (H) x 3.2" (D) 1493.5 (W) x 875.8 (H) x 83.1 (D) mm	67.6" (W) x 39.5" (H) x 3.2" (D) 1717.8 (W) x 1004.8 (H) x 83.1 (D) mm	77.2" (W) x 44.9" (H) x 3.2" (D) 1963 (W) x 1142 (H) x 83.1 (D) mm
Net Weight	40Kgs / 88.1lb	52Kgs / 114.6lb	63Kgs / 138.8lb
Warranty	Refer to your local distributor	Refer to your local distributor	Refer to your local distributor

STANDARD ACCESSORIES

Magnetic Pen	1	1	1
HDMI Cable	1	1	1
Touch USB	1	1	1
Power Cable	1	1	1
Remote	1	1	1

Remark:

Above mentioned specifications are for Standard models and are subject to change without notice.